



AQUAFINE

Water-based 2C coloured coating series

NO CHANCE FOR LIQUIDS AND SHARPS

The AQUAFINE series can be used to create perfectly smooth, aesthetically demanding surfaces of exceptional quality. The coating has good resistance to liquids and common household chemicals, including cleaning agents and disinfectants. It also withstands mechanical influences very well. The abrasion behavior is very good, and the surfaces produced are ring-resistant and scratch-resistant. This makes the AQUAFINE series ideal for demanding indoor applications.

LOW-EMISSION SOLUTION FOR INTERIOR FINISHING

The AQUAFINE series scores with its very low VOC and is a sustainable, easy-to-process solution for all interior finishing. It has good adhesion to all types of wood and is ideal for use on MDF, HDF and foil-laminated boards. No primer is required for foil-laminated boards, only on raw MDF a suitable filler is recommended.

CONTACT US

Calling Teknos is a quick and easy way to get expert advice on the use of AQUAFINE or other Teknos coating products. Our technical customer service is always at your disposal when it comes to developing optimum coating solutions and systems.

MAIN FEATURES

- Good resistance against household chemicals
- High abrasion behaviour
- Low-emission: Less than 3% of VOC
- Good mechanical resistance



Our mission is to extend the life of your products by providing intelligent, technically advanced paint and coating solutions for even better protection – always in close collaboration with our customers.



PRODUCT DATA

VERSIONS	<ul style="list-style-type: none">▪ AQUAFINE 8336-20▪ AQUAFINE 8338-05 GRIP
COLOURS	<ul style="list-style-type: none">▪ In compliance with RAL and NCS S shade cards
GLOSS LEVEL	<ul style="list-style-type: none">▪ Satin matt 20
APPLICATION	<ul style="list-style-type: none">▪ Gravity feed gun▪ Airless (airmix) spraying
CAN SIZE	<ul style="list-style-type: none">▪ 2.46 l, 8.2 l
HARDENER	<ul style="list-style-type: none">▪ 10:1 HYDROPUR 7515-99

DRYING TIMES

DUST DRY AFTER	60 MINUTES
TOUCH DRY AFTER	3 - 4 HOURS
SANDABLE AFTER	12 HOURS
RECOATABLE AFTER	12 HOURS
FULLY DRY AFTER	16 HOURS



**AQUAFINE IS A
REAL ALL-ROUNDER
FOR DEMANDING
INTERIOR SURFACES.**

COATING RECOMMENDATION AQUAFINE 8336

	MDF/HDF	FOIL-LAMINATED BOARDS	PVC	GLASS
PRIMER	HYDROFILL PREMIUM 6338		REINIGUNGSMITTEL 1530-98	ISOPROPYLALKOHOL 0019-98
INTERMEDIATE SANDING	Grain 280-400			
RECOATING	AQUAFINE 8336	AQUAFINE 8336	AQUAFINE 8336	AQUAFINE 8336 mit 1% GLAS ADDITIV 1296-97

COATING RECOMMENDATION AQUAFINE 8338 GRIP

	MDF/HDF	FOIL-LAMINATED BOARDS
PRIMER	HYDROFILL PREMIUM 6338	
INTERMEDIATE SANDING	Grain 220-240	
RECOATING	AQUAFINE 8338 GRIP	AQUAFINE 8338 GRIP